## **DOBLE PROTECTION TESTING**

## F6051

Time Synchronizer



The Doble F6051 is a compact, IRIG-B time protocol converter for when you need precise time synchronization according to industry and security standards. With the Doble F6051, interior time stamping is possible. Use Doble's F6051 in combination with Doble's F-Series Power System Simulators to accept modulated or demodulated signals from station satellite clocks.



- Generates a 1pps signal for accurate time stamping
- Accepts modulated or demodulated signals from station satellite clocks
- IRIG-B signal enters through a BNC connector
- GPS 1pps signal exits through an RS-422 connector

## **BENEFITS**

- Use when you are unable to run a satellite antenna cable outside
- Generate time stamp even if doors and windows cannot be opened for prolonged period due to CIP compliance concerns
- Capable of time synchronization for PMU, IEC 61850, & end-to-end testing where an IRIG-B source is available
- Eliminates tangled satellite cables
- Fits conveniently in your lead bag





## **DOBLE F6051 TECHNICAL SPECIFICATIONS**

GENERAL SPECIFICATIONS		
POWER INPUT/OUTPUT	RANGE	
Power Supply	120-240 volt AC (1 amp max)	
F6051	+12V, max power 15 watts	
F6051 BNC Data input	5 volts peak	
1PPS signal	±1.5V minimum and ±2.5V maximum	
DATA INPUT	FORMAT	

DATA INPUT	FORMAT
IRIG-B BNC input	Unmodulated IRIG-B000 Modulated IRIG-B120
DATA OUTPUT	FORMAT
RS422, 15 pin D type connector	1pps

ENVIRONMENT	RANGE	
Temperature	Operating: 0°C to 50°C (32°F to 122°F) Storage: -20°C to 80°C (-4°F to 176°F)	
DIMENSIONS & WEIGHT		

remperature	Storage: -20°C to 80°C (-4°F to 176°F)	
DIMENSIONS & WEIGHT		
Length	164 mm/ 6. 5 in without end caps, 173 mm/ 6.8 in with end caps	
Width	107.5 mm/ 4.2 in without end caps, 114 mm/ 4.5 in with end caps	
Height	29.5 mm/ 1.2 in without end caps, 36 mm/ 1.43 in with end caps	
Weight	0.45 kg/ 16 oz	



Specifications are subject to change without notice.