# **NLCAMERA**

#### NL CAMERA DATASHEET 90019000-L001

Datasheet version 210819 Compatible with SW version 21H1



#### Saves money and improves energy efficiency

- Pinpoints tiny leaks and shows leak size and cost estimate
- More accurate and faster than other leak detectors and methods

## Data for maintenance, repair plans, and ISO 50001-compatible reporting

• The machine learning-powered NL Cloud service offers advanced analytics and reports

#### Speeds up audits & requires minimal training

- Scans large areas quickly
- Easy to use
- Fits any stage of your maintenance cycle



The NL Camera is a smart acoustic device for locating leaks in compressed air systems. The NL Camera automatically detects leaks by the sound that they emit, even in loud industrial environments. The device is lightweight and easy to use.

The 124 microphones of the NL Camera allow leak detection in a wide field of view and from an extended range. Leak location is up to 10 times faster than with traditional methods. The NL Camera instantly shows the located leaks on the camera view, allowing users to pinpoint and report leaks effortlessly.

The NL Camera analyzes leaks in real time, utilizing its built-in processing power. Users can upload leak data and images to the included NL Cloud for deeper analysis and reporting. The NL Camera Viewer and NL Camera Viewer Pro offline software are for those who cannot use WiFi.





#### NL CAMERA DATASHEET 90019000-L001

Datasheet version 210819 Compatible with SW version 21H1

### **Technical Specifications**

#### **Acoustic Specifications**

Acoustic measurement	124 low-noise MEMS microphones, real-time sound visualization
Dynamic range, low limit	Below -15 dB (frequency-dependent)
Dynamic range, high limit	120 dB (frequency-dependent)
Bandwidth	2–35 kHz
Measurement distance	From 0.3 m (1.0 ft) up to and above 130 m (430 ft)
Leak rate	In typical industrial environment: >0.032 I/min @ 3 bar from 3 m (9.8 ft) >0.05 I/min @ 3 bar from 10 m (32.8 ft) Absolute minimum detection in quiet environment: 0.016 I/min @ 1.2 bar from 0.3 m (1.0 ft)
Leak localization & detection	Automatic leak recognition

#### **User Interface**

Display	5 in, 800 $\times$ 480 resistive touchscreen
Brightness	1000 cd/m2 (adjustable)
Snapshot resolution	800 x 480
Frame rate	25 fps (optical image) / 30 fps (acoustic image)
Zoom	2x digital zoom

#### **Communication and Data Storage**

Wireless data transfer	IEEE 802.11.b/g/n/ac
Storage, internal	32 GB/2000 snapshots (typical)
Storage, external	8 GB USB mass storage, 500 snapshots (typical)

#### **Environmental**

Operating temperature	-10°C – +50°C (14°F – 122°F)
Storage temperature	-20 °C – 70 °C ( -4 °F – 158 °F)
Charging temperature	0°C - +40°C (32°F - 104°F)
Humidity	Recommended 0–90%
Ingress Protection	IP51

#### **Physical data**

Camera size & weight	273 × 170 × 125 mm (10.7 × 6.7 × 4.9 in) 980 g (2.2 lb)
Total weight with Tracer battery	1.9 kg (4.3 lb)
Total weight with RRC2040 battery	1.2 kg (2.7 lb)

#### **NL Analytics & Features**

Leak detection	Automatic, real-time leak recognition
Leak size & cost estimate	Automatic, real-time, on-device
ISO5001-compatible reporting	In the NL Cloud and NL Camera Viewer Pro software
Video recording	Up to 5 minutes
Audio recording	Up to 5 minutes
Video resolution	1640 x 1232
Video frame rate	15 fps

#### **Power Specifications**

Camera power input	Nominal input voltage: 12 V <sub>dc</sub> Max input: 15 V <sub>DC</sub> , 2.5 A
Internal battery	Li-lon 6 Wh (only for backup purposes)

#### **Battery Option RRC2040**

External battery	Li-ion 36.2 Wh, 10.8 V <sub>DC</sub> Use time over 2 h Max output: 12.6 V, 4.0 A
Battery charger	Input: 100.00–240.00 $\rm V_{AC}$ $\pm$ 10% $\sim$ 50/60 Hz 1.70 A @ 100.00 $\rm V_{AC}$
	Max output: 19.00 V $_{\rm DC}$ ± 5%, 3.40 A
Battery size & weight	87 × 65 × 129 mm (3.42 × 2.55 × 5.07 in) 250 g (0.55 lb)

#### **Battery Option Tracer**

External battery	LiFePO <sub>4</sub> 84 Wh, 12 V <sub>DC</sub> Use time up to 7 h, charge time 4-6 h Max output: 13.8 V, 4.0 A
Battery charger	Input: 100-240 $V_{AC} \sim 50/60$ Hz 1.3-1.5 A Max output: 13.8-14.6 $V_{DC'}$ 4 A (depends on the charger provided)
Battery size & weight	90 × 145 × 65 mm (3.5 × 5.7 × 2.6 in) 985 g (2.2 lbs)

#### **Supported Languages**

Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Vietnamese

